

LUT6E


TOUCH 1600nit

6" HDMI FIELD MONITOR

Viewable in sunlight | Focus and exposure easily



High Bright



Resolution



New UI MENU



Custom



In&Out




Power for Camera



>> FEATURES

- 1920x1080 full HD IPS screen, 1600nits daylight viewable
- Touch screen + new menu interface, improve shooting efficient
- User custom 3D LUT, recreate film look (up to 32)
- HDMI input and output, support up to 4K@30Hz
- With Waveform, Vector scope, Histogram, Focus Assist, Mono-chrome etc. functions, can help you accurately exposure and focus every shot.
- HDMI supports LUT loop-out
- Stereo Earphone output
- DC 8.4V power out to power your DSLR camera or mirrorless camera

>> USE PROFESSIONAL REC.709 COLOR CALIBRATION STANDARD



>> SMARTER TOOLS FOR ABSOLUTE PRECISION



3D LUT




Waveform



Vector Scope



Histogram



Anamorphic Mode



Peaking Filter



False Colors



Exposure




Zoom-in



Image Flip



Embedded Audio



Nine Grid

>>> SD card slot import LUT and firmware upgrade




>>> Flexible power supply mode



>>> PARAMETER

Description	6" High Bright 1600nits HDMI On-camera Monitor
Model	LUT6E
Screen size	6" IPS
Display Colors	16.7M (8 bit)
Resolution	1920x1080 pixels
Dot pitch	0.069(L) x 0.069(W) (mm)
Aspect Ratio	16:9
Brightness	1600cd/m2
Contrast	1000:1
Backlight	LED
Response Time	Ton+Toff=35ms
Viewing Angle	80°/80°(L/R) 80°/80°(U/D)
Input	HDMI
Output	HDMI
Power Out	DC OUT 8.4V, Barrel (5.5mm outer, 2.1mm inner; Power DSLR or mirrorless camera)
Audio	3.5mm Stereo Headphone
HDMI Input/ Output Support Format	480i/576i/480p/576p 720p (60/59.94/50/30/29.97/25/24/23.98) 1080i (60/59.94/50) 1080p (60/59.94/50/30/29.97/25/24/23.98) 3840×2160p (30/29.97/25/24/23.98) 4096×2160p (30/29.97/25/24/23.98)
Power Consumption	≤10W
Input Voltage	DC7 ~24V
Power Connector	DC
Battery Plate	F970 Battery Plate
Operating Temperature	-20°C ~ 50°C
Storage Temperature	-30°C ~ 60°C
Install Way	1/4"-20 Thread Point (Right, Bottom)
Unit Size	162Lx93.2Hx29D (mm)
Unit Weight	300g

>> STRUCTURE



>> PACKING LIST

 <p>4K Ultra-Bright FEELWORLD</p> <p>Monitor</p>	 <p>Mini/ Micro HDMI to HDMI Cable</p>	 <p>Tilt Arm</p>	 <p>User manual</p> <p>User manual</p>
---	---	--	---



Zhangzhou Seetec Optoelectronics Technology Co., Ltd

E-mail: sales@feelworld.cn

Tel: +86-596-2182566

Website: www.feelworld.com.cn

Fax: +86-596-2672617

www.seetec.com.cn